

Device marker - EMLP-AL (100X60) - 0830515

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Device marker, Aluminum label, aluminum color, unlabeled, can be labeled with: BLUEMARK ID, BLUEMARK ID COLOR, BLUEMARK CLED, mounting type: adhesive, lettering field size: 100 x 60 mm




Why buy this product

- Stick-on aluminum device marking
- The markers can be marked quickly, easily, and inexpensively with the BLUEMARK CLED



Key Commercial Data

| | |
|------------------------|---|
| Packing unit | 15 STK |
| Minimum order quantity | 15 STK |
| GTIN |  4 046356 718578 |
| GTIN | 4046356718578 |

Technical data

Dimensions

| | |
|------------|--------|
| Length (b) | 60 mm |
| Width (a) | 100 mm |

Ambient conditions

| | |
|--------------------------------|---|
| Recommended storage conditions | -25 °C to +120 °C (>+80 °C slight changes of the material surface possible) |
|--------------------------------|---|

General

| | |
|-------------------------------------|--|
| Color | aluminum color |
| Components | free from silicone, halogen, and cadmium |
| Material | Aluminum |
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 1 |
| Number of individual labels per row | 1 |
| Adhesive | Acrylic |

Device marker - EMLP-AL (100X60) - 0830515

Technical data

General

| | |
|---|-------------------------------------|
| Printability | UV LED technology |
| Device | 5147999 BLUEMARK CLED |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02 |
| Result | Test passed |
| Test specification weathering-resistance | Following ISO 4892-2:2013-03 |
| Test duration | 96 h |
| Wipe resistance test result | Test passed |
| Salt spray test specification | DIN EN 60068-2-11:2000-02 |
| Test duration | 96 h |
| Salt spray testing result | Test passed |
| Alternating condensation climate with SO2 test specification | following DIN 50018:2013-05 |
| Climate level | AHT 1.0 S |
| Cycles | 2 |
| Condensation test result | Test passed |
| Wipe resistance of test specification inscriptions | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result | Test passed |
| Marking mounting type | adhesive |

Standards and Regulations

| | |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>